

FIG. 1



FIG. 2

BLANK

FIG 3



●Sensor positions



Figure 3
μ–BLOX programmer

6.2 Pin Description

Figure 2 shows the pin identification



~~Figure 4~~

μ–BLOX pin-out configuration for the GPS-MS1E


3
GPS
9
Comm
1
106
GPS
Communications Hardware
Port
7
8
107
Analog Digital Support
Correction Hardware
6
106
4
116
FeedBack Controll
5

Communications:

The GPS coordinates at command can be transmitted in many different possible ways. Three of the possible ways included here but not limited to are:

- GPS Receiver with integrated GSM Control Software
- Employing the TDMA Technology
- Employing the CDMA Technology

A) GPS Receiver with integrated GSM Control Software

Overview

The setup requires a GPS receiver (GPS-MS1E-AT), a GSM modem supporting AT interface (GSM 07.05,07.07) and an external controller. The controller reads positions from the GPS receiver and controls the modem. Incorporating the control of the GSM modem into a GPS receiver spares the extra processor, which simplifies the design and saves cost. Below shows the schematic of the communication system.

u-Blox offers an integrated control system for GSM modems with the AT command interface for GPS receivers. This system is designed for autonomous operation. An external controller is not required, however, it can be used for enhanced functionality.



7



FIG. 6

FIG.6A



FIG.6B



FIG.6C



FIG.6D



FIG.6E




H
S
H
S
S
H
S

Volume in space



Area in space



X hysterisis zone

/// exclude zone

□ safe zone



~1



Fig 12



2



Defines Boundary

Defines 2D-3D

Defines Sub Volume

Defines secure/hazard

Program module

Defines Digital filter

Defines Hysteresis Zone

Defines Collar-Base comm

Define Protocall

Define Collar to Collar Comm

Defines digital addresses

Defines method of Correction

Adjusts Correction Parameters